



Shield Coolant/Antifreeze

Phillips 66® Shield Coolant/Antifreeze is formulated to provide extended life protection up to 5 years or 150,000 miles (when flushed and filled according to directions) and is compatible with any antifreeze/coolant used in any vehicle. Concentrate and prediluted 50/50 formulations are available.

Applications

Shield Coolant/Antifreeze is compatible for use in all makes and models of automobiles and light duty trucks regardless of previous antifreeze/coolant used.

Features/Benefits

- Concentrated blend of long-lasting inhibitor
- Extends engine life**
- Compatible with any antifreeze/coolant
- Guards against temperature extremes, rust, corrosion and premature water pump failure
- Available in both concentrated and 50/50 Prediluted formulas
- Meets or exceeds ASTM D3306 and D4985

**Protects your car or light-duty truck for up to 5 years or 150,000 miles (240,000 km) when flushed and filled according to instructions.

**Universal Long Life
Coolant/Antifreeze
FOR USE IN ALL
VEHICLES**

**KEEPING THE
WORLD
RUNNING
SMOOTHLY.**

10-12-2017



Shield Coolant/Antifreeze

Concentrate		
Composition	Typical Values	
Antifreeze Glycols	95.0%	
Corrosion Inhibitors	2.2%	
Total Water	2.8%	
Flash Point	250°F	
Weight per gallon at 60°F	9.35-9.45 lbs	
Silicates	<250 ppm	
Properties	Typical Values	ASTM Method
Chloride	25 ppm	D3634
Specific Gravity at 60°F	1.110-1.145	D1122
Ash Content	2.5%	D1119
pH	7.5-11.0	D1287
Reserve Alkalinity	6	D1121
Water mass %	2.8%	D1123
Freeze Point	-34°F	D1177
Boiling Point	265°F	D1120
Foam Test	150 mL vol., max 5 sec. break, max	D1881

50/50 Prediluted		
Composition	Typical Values	
Antifreeze Glycols	48.0%	
Corrosion Inhibitors	1.1%	
Total Water	49.0%	
Flash Point	-	
Weight per gallon at 60°F	8.8 lbs	
Silicates	<250 ppm	
Properties	Typical Values	ASTM Method
Chloride	33 ppm	D3634
Specific Gravity at 60°F	1.065	D1122
Ash Content	2.5%	D1119
pH	7.5-11.0	D1287
Reserve Alkalinity	3	D1121
Water mass %	49.0%	D1123
Freeze Point	-34°F	D1177
Boiling Point	265°F	D1120
Foam Test	150 mL vol., max 5 sec. break, max	D1881

Protection	Freeze-Up Protection	Boil-Over Protection*	Corrosion Protection
Minimum 50% Antifreeze 50% Water	-34°F	265°F	Meets or exceeds ASTM D3306 ASTM D4985
Maximum 70% Antifreeze 30% Water	-84°F	276°F	

Protection	Freeze-Up Protection	Boil-Over Protection*	Corrosion Protection
Minimum 50% Antifreeze 50% Water	-34°F	265°F	Meets or exceeds ASTM D3306 ASTM D4985

*Using a 15lb. pressure cap in good condition

*Using a 15lb. pressure cap in good condition

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet via <http://www.phillips66.com/EN/products/Pages/MSDS.aspx>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© Phillips 66 Company. Phillips 66® and its respective logos and products are registered trademarks of Phillips 66 Company in the U.S.A. and other countries.