P-Series

Chemical Transfer Pumps for use with agricultural chemicals









P-200H



12VDC
Voltage (Power Source)

P-120H



12V DC
Voltage (Power Source)



Lightweight, Portable

CHEMICAL TRANSFER PUMPS

The GPI Chemical Transfer Pump Series is engineered for dispensing, transferring, and applying large amounts of agricultural chemicals in farming, gardening, and landscaping applications. These pumps can be used with thin to medium viscosity fluids (see viscosity specification for suitability). Portable and tank (or barrel) mount models are available.

SMART DESIGN

Lightweight design and spin collar inlet fitting makes moving between barrels and drums easy

LONG LIFE

Heavy-duty rotary gear design

VERSATILE

12V DC and 115V AC models available

BUILT TO LAST


Constructed of engineered composite and die-cast aluminum for a light-weight, corrosion-resistant product

READY TO GO

Tote-a-Pump (TAP) systems have a 6-foot hose threaded into the inlet that can be dropped into tanks

APPLICATIONS

include agriculture, and landscape or lawn and garden services.







P-Series

Chemical Transfer Pumps for use with agricultural chemicals

LEGACY OF RETAIL FUEL TRANSFER SOLUTIONS

PA-200H-2UR

SKU:	118003-2
Input:	115V (AC)
Motor RPMs:	3250
Motor HP:	1/4
Flow Rate:	8 GPM (30 L/min)
Power Cord:	Factory-installed 12 in., 18 AWG 3-wire pigtail w/a 3 prong grounded NEMA5-15p plug



P-200H-2UR

SKU:	118000-2
Input:	12V (DC)
Fuse:	25 amps
Motor RPMs:	3500
Motor HP:	1/3
Flow Rate:	8 GPM (30 L/min)
Power Cord:	15 ft. (4.6m), 10 AWG, Factory installed, Ring Terminals



P-200H-TAP

SKU:	118602-10
Input:	12V (DC)
Fuse:	25 amps
Motor RPMs:	3500
Motor HP:	1/3
Flow Rate:	8 GPM (30 L/min)
Power Cord:	15 ft. (4.6m), 10 AWG, Factory installed, Ring Terminals



Medium/Thick Chemicals up to 450 CP

SPECS (ALL MODELS)

Туре:	Rotary Gear
Duty Cycle:	30 min on/30 min off
Working Pressure:	16 PSI (1.10 bar)
Max Working Temperature:	-20° F to 125° F (-29° C to 52° C)
Wetted Materials:	PBT Polyester, 303/304 Stainless Steel, Ferrite
Inlet:	1" FNPT
Outlet:	1" FNPT
Mounting Type:	2" FNPT
Suction Pipe:	Not included
Dispensing Hose:	Not included
Nozzle:	Not included
Housing:	Polypropylene
Warranty:	2-yr pump warranty

Refer to manual for wiring instructions

For use with water based agricultural chemicals.

Do not use with gasoline, diesel fuel or micro-encapsulated chemicals

Herbicide Kit 111502-2



P-120H-2UR

SKU:	118000-1
Input:	12V (DC)
Fuse:	20 amps
Motor RPMs:	1650
Motor HP:	1/5
Flow Rate:	12 GPM (45 L/min)
Power Cord:	20 ft. (6.1m), 14 AWG Factory installed, Ring Terminals









GREAT PLAINS INDUSTRIES ///

GreatPlainsIndustries.com | **Product Support:** 800-835-0113 | Support-Pumps@gplains.com